

Océ TDS320 Specifications

System Data



Océ TDS320

Effortless workflow, true reliability

Océ TDS320 printer technology

<i>Technology</i>	Electrophotography (LED) with Organic Photoconductor drum
<i>Resolution</i>	600 dpi
<i>Printer optimization</i>	User specified print optimization modes: Line & Text for excellent line accuracy; Standard for excellent lines plus smooth grays; Poster for excellent grays and smooth solid fills
<i>Fusing technology</i>	Océ Radiant Fusing, instant-on
<i>Toner system</i>	Clean closed toner system, refill while printing

Throughput

<i>Speed</i>	Constant 9 linear ft./min. or 1.8 E size/min. in all print modes
<i>Warm-up time</i>	None, instant-on
<i>Paper path</i>	Optimized, continuous printing speed when printing jobs from different rolls



Media

<i>Media sources</i>	Choice of 1 or 2 roll version plus manual feed; 2 roll version includes integrated stacker for up to 100 prints
<i>Media capacity</i>	Up to 500 ft. per roll with automatic roll switching
<i>Media types</i>	Plain, transparent, recycled, fluorescent and colored paper, films and vellums
<i>Media trimming</i>	Closed system protects cutting device
<i>Output sizes</i>	From "B" to "E" and 36", up to 49 ft. long



Océ TDS320 specifications

Environment

<i>Dimensions</i>	53.5" (W) × 40" (D) × 50" (H)
<i>Weight</i>	Approximately 386 lbs. (1 roll version) 408 lbs. (2 roll version)
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 1340 W, Standby 28 W and Sleep mode 6 W
<i>Sound pressure</i>	Sleep mode 0 dB (A), Standby 24 dB (A) Operating 54 dB (A) according to EN7779 operator position
<i>Safety approvals</i>	TüV GS, CETECOM, CE, (c)UL, FCC°

Océ Power Logic® controller

<i>Platform</i>	Océ Controller with Windows®XP embedded
<i>Memory</i>	512 Mb, expandable to 1.024 Mb
<i>Graphic user interface</i>	Optional monitor
<i>Interfaces</i>	Standard: Ethernet 100/10 Mbits/s. with RJ45
<i>Network protocols</i>	TCP/IP, NetBEUI (smb), Novell (IPX/SPX), FTP, LPD; other protocols supported through an external print server
<i>Power consumption</i>	< 62.5 W controller
<i>Main supply</i>	120/230 V, 50/60 Hz
<i>File formats</i>	HPGL, HPGL2, Calcomp 906/907/951 HPRTL, TIFF 6.0, CALS1, NIRS, C4, ASCII, optional Adobe® PostScript® 3™/PDF
<i>Functionality</i>	<ul style="list-style-type: none">■ File spooling on the controller■ Concurrent receiving / processing / printing■ Océ Settings Editor application: edit and save customized system settings■ Special modes: Standard, Line & Text and Poster■ Multiple prints: up to 999■ Automatic language sensing■ Automatic roll selection and switching■ Plot manipulation: rotation, autoscaling and positioning■ Pen management

Océ Remote Logic® application

Local and remote user communication system with:

<i>Settings Editor</i>	Edit and save customized system settings application:
<i>Supported operating systems</i>	Windows 98, Me, 2000, NT4.0 SP3 and XP; on any other platform and operating system supporting Java 1.1.8 or higher

Océ TDS320 scanner

<i>Technology</i>	CCD, Océ Image Logic® real time image processing hardware
<i>Speed</i>	9 linear ft./min.
<i>Original feed</i>	Face down, right aligned. Automatic feed on/off. Rewind original to front on/off.
<i>Originals</i>	Image width: 8.5" - 36" Original width: 8.5" - 40" Original length: 8.5" - 49 ft.
<i>Exposure control</i>	Automatic background compensation (on/off) manual fine adjustment
<i>Special modes</i>	Line & Text, Photo and Blueprint
<i>Reproduction scale</i>	25% to 400%, adjustable in 1% and programmable fixed steps
<i>Scan-to-file zoom</i>	50% to 200%
<i>Other operating functions</i>	<ul style="list-style-type: none">■ Concurrent copying and printing■ Multicopy mode: 1-99 copies (scan once print many)■ Programmable default settings■ Standard cut or synchro cut modes■ Leading- and trailing-edge adjustment (add or remove up to 15.7")■ Image mirroring
<i>Power consumption</i>	EPA Energy Star® compliant, Operating 140 W, Standby 27 W
<i>Main supply</i>	100/120/230 V, 50/60 Hz
<i>Dimensions</i>	52" (W) × 24" (D) × 45" (H)
<i>Weight</i>	150 lbs.

Océ Scan Logic® software

Océ Scan Logic is an optional scan-to-file software application for the Océ TDS320 multifunctional system.

<i>Applications</i>	Océ Scan Manager, integrated scanning solution and Océ View Station LT for viewing
<i>Scan destinations</i>	6 programmable destinations Scan to Web using FTP Scan to network directory Scan to controller
<i>Resolutions</i>	200, 300, 400 dpi
<i>Data formats</i>	Tiff (G3, G4, uncompressed) CALS Type 1 PDF
<i>Scan modes</i>	Single scan, stream feed productive batch scanning with or without check plot
<i>File naming</i>	Automatically generate unique file names for each scan, change file names at point of scanning
<i>Viewing</i>	View scans at point of scanning
<i>Océ Image Logic</i>	Optimum scan quality with special original modes
<i>Optimization</i>	Scan quality or file size
<i>Ease of use</i>	Scan to file from scanner panel, scan directly to destination
<i>Options</i>	■ Océ View Station for editing and enhancement of scanned documents ■ Océ Batch Processor for automated editing
<i>Minimum requirements</i>	Graphical user interface on Océ Power Logic Controller

Drivers and job-submission software

<i>Océ HDI driver</i>	For AutoCAD (LT) 2000, 2000i, 2002, 2004, 2005 and 2006
<i>Océ WPD</i>	Windows 2000, XP, Windows Server 2003, Windows Terminal Server, Citrix Metaframe
<i>Océ Adobe</i>	Windows 95, 98, ME, NT4.0, 2000, XP and Mac OS 9, X
<i>PostScript® 3 drivers</i>	
<i>OcéPrintExec® LT (optional)</i>	Individual Windows-based productive job creation and submission application with direct device feedback for Windows 2000, XP, and Windows Server 2003





Océ, Océ Power Logic, Océ Remote Logic, Océ Image Logic, Océ Scan Logic and Océ Print Exec Workgroup are registered trademarks of Océ-Technologies B.V. All other trademarks are the priority of their respective owners.



Printing for Professionals

Océ North America, Inc.

5450 North Cumberland Avenue
 Chicago, Illinois 60656
 1-800-714-4427
 1-773-714-4076
 Fax 1-773-714-4056
 www.oceusa.com
 email: info@oceusa.com

Océ-Canada Inc.

4711 Yonge Street, Suite 1100
 Toronto, Ontario, M2N 6K8
 Canada
 1-800-668-1945
 Fax 1-416-224-5778
 email: info.ca@oce.com

Océ Mexico S.A. de C.V.

Ave. Pol. Paseo de la Reforma
 No. 1236 Piso 4
 Col. Sante Fe
 Delegación Cuajimalpa
 México, D.F. 05348
 México
 52-55-5089-8700

© 2005 Océ.

Illustrations and specifications do not necessarily apply to products and services offered in each local market. Technical specifications are subject to change without notice.

ES-24993
 ES-12/05 SLS/AV